

**SINGLE TUBE HEATERS FOR TOWEL RAILS, RANGE CDM-T**

CDM-T single tube heaters are normally used for heating and drying towels in the bathroom.

The **CDM-T** range of heaters are shielded electric heating elements with power feed only at one end. Available in construction **Class I** (main insulation requiring earth plug) and in construction **Class II** (double insulation or reinforced insulation).

Electricfor offers the possibility of personalising the element as far as size, power and suitable attachments for each manufacturer.


The Ø16mm **CDM-T** heaters can incorporate internal safety devices such as a fixed temperature thermostat without automatic reset and a non-resettable thermal fuse to guarantee maximum safety under any working conditions, once these are known.



**Características generales**

	<b>Class I</b>	<b>Class II</b>
<b>Diameter</b>	Ø9,6 - Ø10	Ø16
<b>Safety thermostat</b>	---	Temperature range: from 60 °C to 140 °C to be chosen by the customer depending on performance tests. The thermostat's temperature must be always lower to the holding temperature of the safety thermic fuse.
<b>Safety thermic fuse</b>	Temperature range: from 98 °C to 167 °C to be chosen by the customer depending on performance tests.	
<b>Length "L"</b>	Min 230 mm Max 1450 mm	Min 370 mm Max 1590 mm
<b>Tube material</b>	AISI 304 - AISI 321 - AISI 316L - ly-800 - ly-825	
<b>Fitting</b>	1/2" G - 1" G	

**Ejemplo de resistencia Clase II para toalleros**



**Detail of implementation of the thermostat and safety fuse in a Class II single tube heating element for towel rails.**



**Options of electronic controls able to be connected to CDM-T single tube heaters**

