

Standard models

Model	Dimensions in mm		Area	Weight (dry)	Volume capacity	Filled area weight	Rec. flow rate
	L Length	A Wide					
CSOL-4X8	2310 mm	1200 mm	2,77 m ²	6,8 Kg	9 Lts	5,7 Kg/m ²	720 Lts/h
CSOL-4X10	2920 mm	1200 mm	3,52 m ²	8,2 Kg	11,4 Lts	5,3 Kg/m ²	900 Lts/h
CSOL-4X10,5	3230 mm	1200 mm	3,85 m ²	8,5 Kg	11,7 Lts	5,3 Kg/m ²	900 Lts/h
CSOL-4X12,5	3850 mm	1200 mm	4,62 m ²	10 Kg	14,4 Lts	5,2 Kg/m ²	1200 Lts/h



Accessories

Code	Description	Figure	Notes
CSOL-KPPC	Plastic Panel Connector 4 Pieces: - Upper half clamp - Lower half clamp - Joint - Lock		For each collector you will require 4 sets COSL-KPPC
CSOL-KCPVC	Adaptador DN50		For each bank you will require 2 adaptors
CSOL-PPCEC	End cap		For each collector you will require 2 end caps
CSOL-AF	Helio Roof Mounting Pad 2 Pieces: - Lower clamp - Upper clamp		For each bank you will require 3 Helio roof mounting pads.
CSOL-VB	Vacuum breaker		It is placed in a low place, near the cold in of water and after the valve of the collectors circuit. Always over the level of the swimming pool.

Summary of fittings required

	CSOL-KPPC (Plastic Panel Connector)	CSOL-KCPVC (DN50 Adapto)	CSOL-PPCEC (End cap)	CSOL-AF (Mounting Pads)
For each panel	-	-	-	3
Between 2 panels	2	-	-	-
Between 2 panels across obstruction	4	4	-	-
For each bank ends	4	2	2	-

SOLAR HEAT KIT FOR ABOVE GROUND POOL, CSOL-MINI MODEL

Simple and safe heat source.

Totally manufactured in polypropelene tested in authorised laboratories and proven against the effects of UV radiation and extreme weather conditions. Highly resistant to corrosion, hydrochlorides and other chemical products for pools.

Work with all pool pumps.

Environmentally friendly.

The solar heat kit CSOL-MINI it allows add more panels fast and easy for swimming pools of greater capacity.

The box contains:

- Solar panel 1200 x 6500 mm.
- 2 Flexible hoses
- 2 Clamps

Sizing guide

Round pools		Oval pools	
Dimensions in cm	Panels	Dimensions in cm	Panels
Ø500	1	350 x 700	1
Ø550	1	400 x 550	1
Ø650	1	450 x 900	1 - 2
Ø750	1 - 2	500 x 1000	2
Ø850	2	550 x 1050	2



Model	Dimensions en mm		Area
	Length	Wide	
CSOL-MINI	6500 mm	1200 mm	7,8 m ²