

Single-pole bulb and capillary thermostats



Bulb and capillary thermostats to include in the Europa Range

Single-pole snap action thermostats. 3 to 5 °C differential depending on temperate scales. Bulb and capillaries in copper up to 160°C, and in stainless steel for over 160°C. Connection to 6.3 mm fastons.

The thermostat units for each of the temperatures comprise the standard thermostat with its respective buttons, cover and connection screws.

Code	Thermostat range	Range	Characteristics	Max current (~240 V)	Weight in Kg
3509310324	CA	0 / 40 °C	Bulb in copper Ø6,5x142 mm Capillary 1m. 3 Faston (*)	16 A	0,11
3509310320	CA	0 / 90 °C	Bulb in copper Ø6,5x66 mm Capillary 1m. 3 Faston (*)	16 A	0,11
3509310321	CA	0 / 120 °C	Bulb in copper Ø6,5x66 mm Capillary 1m. 3 Faston (*)	16 A	0,11
3509310322	CA	0 / 200 °C	Bulb in S. Steel Ø5x98 mm Capillary 1m. 3 Faston (*)	16 A	0,11
3509310323	CA	0 / 320 °C	Bulb in S. Steel Ø3x195 mm Capillary 1m. 3 Faston (*)	16 A	0,11
517350000	CT1	0 / 90 °C	Bulb in copper Ø6x99 mm Capillary 1m. 2 Faston	20 A	0,06
517355000		Button + Face plate 0 / 90 °C			0,01
517352000	CT2	30 / 160 °C	Bulb in copper Ø6x88 mm Capillary 1m. 2 Faston	20 A	0,06
517357000		Button + Face plate 30 / 160 °C			0,01

NON-pluggable cane thermostats



Bulb and capillary thermostats to include in the Europa Range

Three-pole snap action thermostats. 2 to 13°C differential depending on temperate scales. Bulb and capillaries in stainless steel. Connection to 6.3mm fastons.

Code	Thermostat range	Range	Characteristics	MAXimum intensity (~240 V)	Weight in Kg
517370000	EG	1 / 40 °C	Bulb in copper Ø6x215 mm Capillary 880 mm	16 A	0,19
517370001		Botón escala 0 / 40 °C			0,02
517371000	EG	28 / 85 °C	Bulb in copper Ø6x129 mm Capillary 880 mm	16 A	0,19
517371001		Botón escala 30 / 85 °C			0,02
517372000	EG	36 / 125 °C	Bulb in copper Ø6x138 mm Capillary 880 mm	16 A	0,19
517372001		Botón escala 30 / 120 °C			0,02
517373000	EG	60 / 200 °C	Bulb in S. Steel Ø6x142 mm Capillary 880 mm	16 A	0,19
517373001		Button scale 60 / 200 °C			0,02
517374000	EG	50 / 300 °C	Bulb in S. Steel Ø6x77 mm Capillary 880 mm	16 A	0,19
517374001		Button scale 50 / 300 °C			0,02

Rod thermostats



Single-pole rod thermostats. 5 to 10°C differential depending on temperature scales. Connection by leads through side inputs.

Code	Description	Thermostat range	Operation temperatures		Characteristics	Maximum current (~240 V)
			Control (Automatic reset)	Safety (Manual reset)		
517330000	TER-CO-165-0-80-NEF	NEF	0 / 80 °C	---	Sheath Ø7,5x165 mm	20 A
517335000	TER-CO-265-5-80-NEF	NEF	5 / 80 °C	---	Sheath Ø7,5x265 mm	20 A
517337000	TER-CO-265-45-120-NEF	NEF	45 / 120 °C	---	Sheath Ø7,5x265 mm	20 A
517358000	TER-CO-165-0-73-87-NEF	NEF	-10 / 73 °C	87 °C	Sheath Ø7,5x165 mm	20 A
517347000	TER-SV-280-45-95-NEF	NEF	---	45 / 95 °C	Sheath Ø7,5x280 mm	16 A

ACCESSORIES FOR THERMOSTATS

Code	Description
570004330	Mounting clip for bulb thermostat Ø _{nominal} 7,5 mm to sheath Ø _{int} 3,5 to 8 mm
570004331	Mounting clip for bulb thermostat Ø _{nominal} 6 mm to sheath Ø _{int} 3,5 to 7 mm
570004332	Mounting clip for bulb thermostat Ø _{nominal} 8 mm to sheath Ø _{int} 3,5 to 12 mm